

# SCREWDRIVERS WITH SLIP CLUTCH

COMPACT AND LIGHT

▶ EASY TO HANDLE

▶ HIGH PRODUCTIVITY

TIGHTEN

▶ METRIC AND SELF-THREADING SCREWS

▶ DIFFERENT APPLICATIONS

ERGONOMIC GRIPS

▶ COMFORTABLE TOOL GRIP

▶ GUARANTEED COMFORT

UNTIGHTEN

▶ BY PRESSING ON THE REVERSIBILITY BUTTON

▶ IDEAL TO DISASSEMBLE

STURDY AND LONG-LASTING

▶ LOW MAINTENANCE

▶ CONTINUOUS EFFICIENCY



START LEVER

CODE	MODEL	Nm	TORQUE RANGE in lb	SPEED (rpm)	Kg	WEIGHT lb
114812951	1W26A8S	1,5÷8	13.275÷70.8	1.000	0,82	1.804
114812952	1W26A10S	1,5÷10	13.275÷88.5	500	0,82	1.804

Air inlet: 1/4" gas | Accessory drive:  $\odot$  F 1/4" | Recommended hose bore:  $\emptyset$  8 mm



PUSH BUTTON

114812551	3W26A8S	1,5÷8	13.275÷70.8	900	0,98	2.156
114812552	3W26A10S	1,5÷10	13.275÷88.5	450	0,98	2.156

Air inlet: 1/4" gas | Accessory drive:  $\odot$  F 1/4" | Recommended hose bore:  $\emptyset$  8 mm