

Chipping Hammers / Flux Scaling Hammers

Chipping Hammers Spring retainer type

The chipping hammers are used for a lot kind of chipping application.



AA-00SP(R)
AA-00SP(H)



AA-0SP(R)
AA-0SP(H)



AA-1ASP(R)
AA-1ASP(H)



AA-2SP(R)
AA-2SP(H)



AA-3SP(R)
AA-3SP(H)



AA-75SP(R)
AA-75SP(H)



AA-15XSP(R)
AA-15XSP(H)



AA-3XBSP(R)
AA-3XBSP(H)

Recommended air pressure 0.6MPa(6kgf/cm², 85psi)

Model	code	Blow per minute	Piston diameter		Piston stroke		Overall length		Mass		Air inlet thread	Hose size		Average air consumption	
		min ⁻¹	mm	in	mm	in	mm	in	kg	lb	Rc or NRT	mm	in	m ³ /min	ft ³ /min
AA-00SP(R)	30076	3800	18	11/16	45	1 ³ / ₄	233	9 ³ / ₁₆	2.1	4.6	1/4	9.5	3/8	0.3	10.6
AA-00SP(H)	30077	3800	18	11/16	45	1 ³ / ₄	233	9 ³ / ₁₆	2.1	4.6	1/4	9.5	3/8	0.3	10.6
AA-0SP(R)	30080	3200	18	11/16	75	3	281	11 ¹ / ₁₆	2.4	5.3	1/4	9.5	3/8	0.35	12.4
AA-0SP(H)	30081	3200	18	11/16	75	3	281	11 ¹ / ₁₆	2.4	5.3	1/4	9.5	3/8	0.35	12.4
AA-1ASP(R)	30084	2800	24	15/16	51	2	300	11 ¹³ / ₁₆	4.2	9.2	3/8	12.7	1/2	0.4	14.1
AA-1ASP(H)	30085	2800	24	15/16	51	2	300	11 ¹³ / ₁₆	4.2	9.2	3/8	12.7	1/2	0.4	14.1
AA-2SP(R)	30090	2400	28	1 ¹ / ₈	51	2	312	12 ⁵ / ₁₆	5.9	13.0	3/8	12.7	1/2	0.5	17.7
AA-2SP(H)	30091	2400	28	1 ¹ / ₈	51	2	312	12 ⁵ / ₁₆	5.9	13.0	3/8	12.7	1/2	0.5	17.7
AA-3SP(R)	30100	2000	28	1 ¹ / ₈	76	3	339	13 ³ / ₈	6.2	13.6	3/8	12.7	1/2	0.5	17.7
AA-3SP(H)	30101	2000	28	1 ¹ / ₈	76	3	339	13 ³ / ₈	6.2	13.6	3/8	12.7	1/2	0.5	17.7
AA-75SP(R)	30102	2000	28	1 ¹ / ₈	76	3	344	13 ⁹ / ₁₆	6.2	13.6	3/8	12.7	1/2	0.5	17.7
AA-75SP(H)	30103	2000	28	1 ¹ / ₈	76	3	344	13 ⁹ / ₁₆	6.2	13.6	3/8	12.7	1/2	0.5	17.7
AA-15XSP(R)	30327	2000	24	15/16	70	2 ³ / ₄	342	13 ⁷ / ₁₆	4.9	10.8	3/8	12.7	1/2	0.5	17.7
AA-15XSP(H)	30328	2000	24	15/16	70	2 ³ / ₄	342	13 ⁷ / ₁₆	4.9	10.8	3/8	12.7	1/2	0.5	17.7
AA-3XBSP(R)	30110	2000	28	1 ¹ / ₈	76	3	347	13 ¹¹ / ₁₆	6.9	15.2	3/8	12.7	1/2	0.5	17.7
AA-3XBSP(H)	30111	2000	28	1 ¹ / ₈	76	3	347	13 ¹¹ / ₁₆	6.9	15.2	3/8	12.7	1/2	0.5	17.7

Specifications are subject to change without notice.

Flux Scaling Hammers

Flux scaling hammers are handle and used for chipping stone, metal, concrete, brick and weld flux.



NF-00
(Cap Chisel Holder)



NF-0 (Cap Chisel Holder)



NF-20



NF-1SH (Slide Ball Retainer)



NFB-25H (Slide Ball Retainer)



NF-25F (Slide Ball Retainer)

Recommended air pressure 0.6MPa(6kgf/cm², 85psi)

Model	code	Blow per minute	Piston diameter		Piston stroke		Overall length		Mass		Air inlet thread	Hose size		Average air consumption	
		min ⁻¹	mm	in	mm	in	mm	in	kg	lb	Rc or NRT	mm	in	m ³ /min	ft ³ /min
NF-00	30038	6500	14	9/16	12	1/2	164	6 ⁷ / ₁₆	0.55	1.2	1/4	6.3	1/4	0.23	8.1
NF-0	30039	5500	18	11/16	18	11/16	177	6 ¹⁵ / ₁₆	0.8	1.8	1/4	6.3	1/4	0.23	8.1
NF-20	30447	5000	20	13/16	17	11/16	200	7 ⁷ / ₈	0.88	1.9	1/4	6.3	1/4	0.15	5.3
NF-1SH	30040	4800	22	7/8	22	7/8	187	7 ³ / ₈	0.94	2.1	1/4	6.3	1/4	0.25	8.8
NF-25F	30044	4800	25	1	17	11/16	225	8 ⁷ / ₈	1.5	3.3	1/4	9.5	3/8	0.2	7.1
NFB-25H	30043	4000	25.4	1	23	7/8	265	10 ⁷ / ₁₆	2.0	4.4	1/4	9.5	3/8	0.55	19.4

Specifications are subject to change without notice.