

Vertical Grinders / CNS Grinders

Vertical Grinders

These direct-drive grinders provide strong grinding power.

■ Lever Type

● 180mm(7") Built-in governor



NVG-180SL

● 230mm(9") Built-in governor



NVG-230SL

■ Safety Lever Type

● 180mm(7") Built-in governor




NVG-180SLW

● 230mm(9") Built-in governor



NVG-230SLW



Recommended air pressure 0.6MPa(6kgf/cm², 85psi)

| Model | code | Capacity (Wheel size) | | Spindle thread | Max.free speed | Overall length | | Mass | | Max. output | | Air inlet thread | Hose size | | Average air consumption | |
|------------|-------|-----------------------|---------------|----------------|----------------|----------------|--------------------------------|------|-----|-------------|------|------------------|-----------|-----|-------------------------|------|
| | | mm | in | | | in | min ⁻¹ | mm | in | kg | lb | | kw | ps | Rc or NPT | mm |
| NVG-180SL | 10119 | 180x6x22 | 7 X 1/4 X 7/8 | 5/8"-11UNC | 7100 | 187 | 7 ³ / ₈ | 3.8 | 8.4 | 1.87 | 2.54 | 3/8 | 12.7 | 1/2 | 1.1 | 38.8 |
| NVG-230SL | 10122 | 230x6x22 | 9 X 1/4 X 7/8 | 5/8"-11UNC | 5900 | 189 | 7 ⁷ / ₁₆ | 4.2 | 9.2 | 1.87 | 2.54 | 3/8 | 12.7 | 1/2 | 1.1 | 38.8 |
| NVG-180SLW | 10120 | 180x6x22 | 7 X 1/4 X 7/8 | 5/8"-11UNC | 7100 | 187 | 7 ³ / ₈ | 3.8 | 8.4 | 1.87 | 2.54 | 3/8 | 12.7 | 1/2 | 1.1 | 38.8 |
| NVG-230SLW | 10123 | 230x6x22 | 9 X 1/4 X 7/8 | 5/8"-11UNC | 5900 | 189 | 7 ⁷ / ₁₆ | 4.2 | 9.2 | 1.87 | 2.54 | 3/8 | 12.7 | 1/2 | 1.1 | 38.8 |
| NVG-230HLW | 10101 | 230x6x22 | 9 X 1/4 X 7/8 | 5/8"-11UNC | 5900 | 189 | 7 ⁷ / ₁₆ | 4.2 | 9.2 | 1.87 | 2.54 | 3/8 | 12.7 | 1/2 | 1.1 | 38.8 |

Specifications are subject to change without notice.

CNS Grinders

The CNS Grinder is most suitable for removing block scale, oxide layer, or paint and provides uniform and beautiful facing.


■ Safety Grip Type



NHG-65G



NHG-75G



*CNS Wheel turn to page 36.

Recommended air pressure 0.6MPa(6kgf/cm², 85psi)

| Model | code | Capacity (Wheel size) | | Max.free speed | Overall length | | Height | | Mass | | Max. output | | Air inlet thread | Hose size | | Average air consumption | |
|---------|-------|-----------------------|---|----------------|-------------------|----------------------------------|--------|----|------|-----|-------------|------|------------------|-----------|-----------|-------------------------|------|
| | | mm | in | | min ⁻¹ | mm | in | mm | in | kg | lb | kw | | ps | Rc or NPT | mm | in |
| NHG-65G | 10044 | 65x26x9.5 | 2 ¹ / ₂ X 1 X 3/8 | 14000 | 310 | 12 ³ / ₁₆ | - | - | 1.3 | 2.9 | 0.58 | 0.79 | 1/4 | 9.5 | 3/8 | 0.55 | 19.4 |
| NHG-75G | 10074 | 100x26x9.5 | 4 X 1/4 X 5/8 | 6000 | 328 | 12 ¹⁵ / ₁₆ | - | - | 1.7 | 3.7 | 0.77 | 1.05 | 1/4 | 9.5 | 3/8 | 0.45 | 15.9 |

Specifications are subject to change without notice.