

Sanders / Wire Brush Sanders

Sanders

Comfortable and Compact - perfectly balanced, easy to handle and excellent power.

■ Lever Type

● 100mm(4")



NSG-100

■ Safety Grip Type

● 125mm(5")



NSG-125

● 150mm(6")



NSG-150X

● 180mm(7")




NSG-180XC

■ Safety Lever Type

● 180mm(7")



NSG-180XCLW
(Safety Lever Type)



Recommended air pressure 0.6MPa(6kgf/cm², 85psi)

Model	code	Capacity (Wheel size)		Max.free speed min ⁻¹	Overall length		Height		Mass		Air inlet thread Rc or NPT	Hose size		Average air consumption	
		mm	in		mm	in	mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
NSG-100	10176	100x16	4 x 5/8	13000	160	6 5/16	102	4	0.9	2.0	1/4	6.3	1/4	0.4	14.1
NSG-125	15313	125x16	5 x 7/8	11000	190	7 1/2	190	7 1/2	1.5	3.3	1/4	9.5	3/8	0.68	24
NSG-150X	15309	150x22	6 x 7/8	8400	209	8 1/4	179	7 1/16	2.2	4.8	3/8	12.7	1/2	0.65	23.0
NSG-180XC	15307	180x22	7 x 7/8	7600	209	8 1/4	179	7 1/16	2.2	4.8	3/8	12.7	1/2	0.65	23.0
NSG-180XCLW	15308	180x22	7 x 7/8	7600	239	9 7/16	190	8 1/2	2.4	5.3	3/8	12.7	1/2	0.65	23.0

Specifications are subject to change without notice.

Wire Brush Sanders

The Wire Brush Sanders are specialized wire-brushing machines. These are used to remove rust and paint or to descale beads after welding.

■ Safety Grip Type





NAG-70WA

■ Safety Lever Type



NAG-70WALW



Recommended air pressure 0.6MPa(6kgf/cm², 85psi)

Model	code	Capacity (Wheel size)		Max.free speed min ⁻¹	Overall length		Height		Mass			Air inlet thread Rc or NPT	Hose size		Average air consumption		
		mm	in		mm	in	mm	in	kg	lb	kw		ps	mm	in	m ³ /min	ft ³ /min
NAG-70WA	10744	120x22	4 3/4 x 7/8	6500	257	10 1/8	109	4 5/16	2.8	6.2	1.2	1.6	3/8	12.7	1/2	0.9	31.8
NAG-70WALW	10714	120x22	4 3/4 x 7/8	6500	276	10 7/8	109	4 5/16	2.8	6.2	1.2	1.6	3/8	12.7	1/2	0.9	31.8

Specifications are subject to change without notice.